

Oy Ekotuantanto Ab

Ecoproduction Ltd

Sand Separator

EKOSEP®



All Our Solutions are
Customized Not Compromised

TECHNICAL DATAS

| TYPE | SASE 05 | SASE 10 | SASE 20 | SASE 30 | SASE 40 |
|----------------|----------------|----------------|----------------|----------------|----------------|
| Capacity m3/H | 5 | 10 | 25 | 50 | 75 |
| Tank volume m3 | 0,5 | 1 | 2 | 3 | 4 |

| Drive motor | SASE 05 | SASE 10 | SASE 20 | SASE 30 | SASE 40 |
|--------------------|----------------|----------------|----------------|----------------|----------------|
| power, kW | 0,37 | 0,37 | 0,37 | 0,37 | 0,37 |

Materials

| | | |
|---------------|-----------------|--|
| Tank | Stainless steel | |
| Screw | Stainless steel | |
| Shaft | Stainless steel | |
| Trough | Stainless steel | |
| Wearing plate | Plastic | |

Typical applications are:

- * domestic sewage treatment plans
- * food processing industry
- * textile industry
- * tanneries

to client We have delivered our equipment in:

- * Europe
- * The Far East
- * Eastern Europe
- * Russia
- * Africa
- * South America
- * North America
- * Asia

SEPA Sand separator is designed to separate coarse materials from waste water.

The screw length and screw angle are usually tailored according to requirements and layout.

The trough has been equipped with wearing plate under the screw.

The drive motor has been located to the upper end of the screw.

Oy Ekotuotanto Ab

Vattuniemenkatu 27, 00210 Helsinki
Tel.+358-400-482440, Fax.+358-19-437237
Web; www.ekotuotanto.fi
Email; avi@ekotuotanto.fi